


THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.

REV.	ECN NO.	DATE	SIGN	DESCRIPTION
A		2020/01/20	Vicky	Initial Released



- Note:
- * \varnothing Important Dimension
 - * Waterproof Rate: IP68, Mated
IP68: 1M depth of water in 24hours
 - * Connector: Thermoplastic, Black
 - * Pin: Copper Alloy, Gold Plated
 - * Cable: UL21388, PVC Jacket, Black
 - * Cable Length Tolerance: 0.5M: +60/-0mm
01M: +60/-0mm
02~03M: +120/-0mm
04~05M: +160/-0mm
06~10M: ±100mm
11~20M: ±200mm
21~30M: ±300mm
31~99M: ±500mm

UNIT:mm TOLERANCE $\pm 0.5\text{mm}$	TITLE ACC, XLOK, B-10A, DB-ENDED FM			Amphenol LTW 安費諾亮泰企業股份有限公司	ITEM NO	DRAWN BY Vicky	DATE 2020-01-20
	SCALE 1:2	SIZE A4	SHEET 1 OF 2		DWG NO AB-BBXXFL-BBHL-QDXXX	CHECKED BY Rita	DATE 2020-01-20
	REV. A	WC-REV. A.5	\varnothing : Inspection item		CUSTOMER ALTW	APPROVED BY Max	DATE 2020-01-20

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.

3P	PVC	6.5	16	AB-BB03FL-BBHL-QDXXX
2P		6.0		AB-BB02FL-BBHL-QDXXX
Contacts	Cable Jacket	Cable OD	AWG	Item No.

AB-BB XX FL-BBHL-QD XXX

02: 2Pin
03: 3Pin

XXX: 0.5~99Meters
A05: 0.5 Meter
001: 01 Meter
002: 02 Meters
:
099: 99 Meters

Pin Out	2	Red	紅	3	Red	紅
	1	Black	黑	2	Brown	紅棕
				1	Black	黑
	Pin #	Wire		Pin #	Wire	
C2						
	2P			3P		
C1						
	2P			3P		

Pin Assignments Front View

UNIT:mm	
TOLERANCE	±0.5mm

TITLE ACC, XLOK, B-10A, DB-ENDED FM			
SCALE 1:2	SIZE A4	SHEET 2 OF 2	
REV. A	WC-REV. A.5	QC: Inspection item	

Amphenol LTW

安費諾亮泰企業股份有限公司

ITEM NO	DRAWN BY Vicky	DATE 2020-01-20
DWG NO AB-BBXXFL-BBHL-QDXXX	CHECKED BY Rita	DATE 2020-01-20
CUSTOMER ALTW	APPROVED BY Max	DATE 2020-01-20