




THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.

REV.	ECN NO.	DATE	SIGN	DESCRIPTION
A		2020/01/20	Vicky	Initial Released



- Note:
- * \varnothing Important Dimension
 - * Waterproof Rate: IP68, Mated
IP68: 1M depth of water in 24hours
 - * Connector: Thermoplastic, Black
 - * Pin: Copper Alloy, Gold Plated
 - * Cable: UL21388, PVC Jacket, Black
 - * Cable Length Tolerance: 0.5M: +60/-0mm
01M: +60/-0mm
02~03M: +120/-0mm
04~05M: +160/-0mm
06~10M: ±100mm
11~20M: ±200mm
21~30M: ±300mm
31~99M: ±500mm

UNIT: mm		TITLE	ACC, XLOK, B-10A, DB-ENDED MF		
TOLERANCE	±0.5mm	SCALE	1:2	SIZE	A4
		REV.	A	WC-REV.	A.5
		SHEET	1	OF	2
		\varnothing : Inspection item			

Amphenol LTW
安費諾亮泰企業股份有限公司

ITEM NO.	DRAWN BY	DATE
	Vicky	2020-01-20
DWG NO.	CHECKED BY	DATE
AB-BBXXML-BBFR-QDXXX	Rita	2020-01-20
CUSTOMER	APPROVED BY	DATE
ALTW	Max	2020-01-20

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.

4P	PVC	6.8	16	AB-BB04ML-BBFR-QDXXX
3P		6.5		AB-BB03ML-BBFR-QDXXX
2P		6.0		AB-BB02ML-BBFR-QDXXX
Contacts	Cable Jacket	Cable OD	AWG	Item No.

AB-BB XX ML-BBFR-QD XXX

02: 2Pin
03: 3Pin
04: 4Pin

XXX: 0.5~99Meters
A05: 0.5 Meter
001: 01 Meter
002: 02 Meters
:
099: 99 Meters

Pin Out	2 1	Red Black	紅 黑	3 2 1	Red Brown Black	紅 棕 黑	4 3 2 1	Orange Red Brown Black	橙 紅 棕 黑
	Pin #	Wire	Pin #	Wire	Pin #	Wire	Pin #	Wire	
C2									
	2P		3P		4P				
C1									
	2P		3P		4P				

Pin Assignments Front View

UNIT:mm		TITLE	ACC, XLOK, B-10A, DB-ENDED MF		
TOLERANCE	±0.5mm	SCALE	1:2	SIZE	A4
		REV.	A	WC-REV.	A.5
				SHEET	2 OF 2
					QC: Inspection item

Amphenol LTW
安費諾亮泰企業股份有限公司

ITEM NO	DRAWN BY	DATE
DWG NO	CHECKED BY	DATE
CUSTOMER	APPROVED BY	DATE
ALTW	Vicky Rita Max	2020-01-20 2020-01-20 2020-01-20