




THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.

REV.	ECN NO.	DATE	SIGN	DESCRIPTION
A		2020/01/08	Ruru	Initial Released



Note:
 * \varnothing Important Dimension.
 * Waterproof Rate: IP68, Mated.
 IP68: 1M depth of water in 24 hours.
 * Connector: Thermoplastic, Black.
 * Pin: Copper Alloy, Gold Plated.
 * Cable: SJTW, PVC Jacket, Black.
 * Cable Length Tolerance: 0.5M: +60/-0mm
 01M: +60/-0mm
 02~03M: +120/-0mm
 04~05M: +160/-0mm
 06~10M: ±100mm
 11~20M: ±200mm
 21~30M: ±300mm
 31~99M: ±500mm



UNIT: mm		
TOLERANCE	±0.5 mm	

TITLE ACC, XLOK, C-20A, DB-ENDED FF		
SCALE 1:2	SIZE A4	SHEET 1 OF 2
REV. A	WC-REV.	\varnothing : Inspection item

Amphenol LTW
 安費諾亮泰企業股份有限公司

ITEM NO.	DRAWN BY Ruru	DATE 2020-01-08
DWG NO. AB-CCXXFR-CCBR-QEXXX	CHECKED BY Rita	DATE 2020-01-08
CUSTOMER ALTW	APPROVED BY Max	DATE 2020-01-08

3P		PVC	11.7	12	AB-CC03FR-CCBR-QEXXX
2P			10.7		AB-CC02FR-CCBR-QEXXX
Contacts	Cable Jacket	Cable OD	AWG	Item No.	



UNIT:mm

TOLERANCE
± 0.5 mm

TITLE ACC, XLOK, C-20A, DB-ENDED
FF

SCALE 1:2 SIZE A4 SHEET 2 OF 2

REV. A WC-REV. : Inspection item

Amphenol LTW
安費諾亮泰企業股份有限公司

ITEM NO	DRAWN BY Ruru	DATE 2020-01-08
DWG NO AB-CCXXFR-CCBR-QEXXX	CHECKED BY Rita	DATE 2020-01-08
CUSTOMER ALTW	APPROVED BY Max	DATE 2020-01-08

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.