




REV.	ECN NO.	DATE	SIGN	DESCRIPTION
B	LE31610203~206	2016/01/11	Ruru	Change Logo & Note & Ball-marker

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.



① BDU-08AFMM-LL6000  $\Delta$   
Color: Black

- $\Delta$ Note:
- \*  $\Delta$  Important Dimension To Check.
  - \* Waterproof Rate: IP66
  - \* Connector: Nylon+GF, Black
  - \* Male Pin: Copper Alloy, Gold Plated
  - \* O-Ring: EPDM, Black
  - \* Lock Nut: Nylon+GF, Black
  - \* Cable: UL2464(24AWG\*2C+26AWG\*6C)+Drain+AL/My(UV Resistant )OD=5.5mm, Black
  - \* Cable Length Tolerance: 01M:  $\pm$ 40mm  
02M~05M:  $\pm$ 60mm  
06M~10M:  $\pm$ 100mm  
11M~30M:  $\pm$ 200mm  
31M~99M:  $\pm$ 500mm



Pin Assignments  
Front View

8	Red	(26AWG)
7	Pink	(26AWG)
6	Gray	(26AWG)
5	Brown	(24AWG)
4	Green	(26AWG)
3	White	(26AWG)
2	Blue	(24AWG)
1	Yellow	(26AWG)
Conn	Wire Color	Pin Out

UNIT:mm		TITLE	<b>Amphenol LTW</b>		ITEM NO	DRAWN BY	DATE
TOLERANCE	$\pm 0.5$ mm	BDU-08AFMM-L180 To Cable	安費諾亮泰企業股份有限公司		DWG NO	Ruru	2016/01/11
SCALE	1/1	SHEET	1 OF 1	CUSTOMER	BDU-08AFMM-LL6AXX	CHECKED BY	Rita
REV.	B	SIZE	A4	APPROVED BY	ALTW	Lisa	DATE
		QC	: Inspection Item				2016/01/11